


4K Ultra HD IP IR Water-resistant
Vandal Dome


EYEONET®



Features

- H.265 main profile video compression technology, high compression ratio, stable stream control
- 4K (3840 x 2160) full real time coding
- 2.8mm fixed lens
- ICR auto switch, true day / night
- 20m IR night view distance
- 3D DNR, digital WDR
- Smart analysis including object removal, line crossing detection and intrusion detection, etc.
- Support defogging, HLC, BLC, digital image stabilization and defect correction to meet different situations
- Support local CVBS video output and one-way audio
- PoE power supply / DC12V
- Support P2P, smart phone, iPad, remote monitoring
- IP66 & IK10 ingress protection
- Support three streams

Dimensions



Specifications

Specifications	Model	CAM-IP639E8G-28-4K
Camera		
Image Sensor	1 / 2.5 \"CMOS	
Image Size	3840 × 2160	
Electronic Shutter	1 / 25 s ~ 1 / 100000 s	
Iris Type	Fixed Iris	
Min. Illumination	0.068lux @ F2.0, AGC ON; 0.024lux @ F1.2, AGC ON; 0 lux with IR	
Lens	2.8 mm	
Lens Mount	M12	
Day & Night	ICR	
Wide Dynamic Range	Digital WDR	
BLC	Yes	
HLC	Yes	
Defogging	Yes	
Digital NR	3D DNR	
Angle Adjustment	Pan : 0°~355°, Tilt : 0°~67°, Rotation : 0°~355°	
Image		
Video Compression	H.265 MP; H.264 BP / MP / HP; MJPEG	
Resolution	4K (3840 × 2160), 4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240	
Main Stream	60Hz : 4K (1~20fps) / 2K (1~30fps) / 3MP (1~30fps) / 1080P (1~30fps) / 50Hz : 4K (1~20fps) / 2K (1~25fps) / 3MP (1~25fps) / 1080P (1~25fps)	
Bit Rate	128Kbps~10Mbps	
Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, Anti-flicker, BLC, HLC, defog, smart IR etc. adjustable through client or web browser	
ROI	Support	
Interfaces		
Network	RJ45 × 1	
Functions		
Remote Monitoring	Web browser, CMS remote control	
Online Connection	Support simultaneous monitoring for up to 10 users and multi-stream transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, HTTPS, QoS, 802.1X, SNMP	
Interface Protocol	ONVIF	
Storage	Network remote storage	
Smart Alarm	Motion alarm	
PoE	Yes	
IR Distance	20 m	
Ingress Protection	IP66, IK10	
Others		
Power Supply	DC12V / PoE	
Power Consumption	< 6W	
Operating Environment	Temperature: -30°C~60°C; RH: <95%(non-condensing)	
Dimensions (mm)	Φ117 × 90	
Weight (net)	Approx. 0.58KG	
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)	